

## Schottky Barrier Diode 1A, 40V Type

### ■ GENERAL DESCRIPTION

XB01SB04A2BR employs 1A level of a schottky diode in a small package equivalent to SOD-123 package. It is suitable for compact, low profile circuit designs. By giving the series low VF and low IR characteristics, it minimizes power supply loss.

### ■ APPLICATIONS

- Rectification of compact DC/DC converter
- Surge absorption caused by counter force of compact motors
- Energy-saving for notebook PCs, hand-set
- Protection against reverse connection of battery

### ■ FEATURES

**1A, 40V Type**

**Low VF 0.49V @1A (TYP.)**

**Low IR 4  $\mu$  A @40V (TYP.)**

**Small Package : SOD-123**

### ■ ABSOLUTE MAXIMUM RATINGS

Ta = 25°C

PARAMETER	SYMBOL	RATINGS	UNIT
Repetitive Peak Reverse Voltage	VRM	40	V
Reverse Voltage (DC)	VR	40	V
Forward Current (Average)	IF(AV)	1	A
Non Continuous Forward Surge Current*1	IFSM	10	A
Junction Temperature	Tj	125	°C
Storage Temperature Range	Tstg	-55~+150	°C

\*1: Non continuous high amplitude 60Hz half-sine wave.

### ■ ELECTRICAL CHARACTERISTICS



Ta=25°C

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNITS
			MIN.	TYP.	MAX.	
Forward Voltage (DC)	VF	IF=1A	—	0.49	0.54	V
Reverse Current (DC)	IR	VR=40V	—	4	200	$\mu$ A
Inter-Terminal Capacity	Ct	VR=10V, f=1MHz	—	35	—	pF
Reverse Recovery Current *2	trr	IF=IR=10mA, irr=1mA, RL=100 $\Omega$	—	25	—	ns

Note) 1. This product has a weakness for an electroshock such as electrostatic.


Please be careful of an electrification to human body and an electric leakage in the application.

2. \*2: trr measurement circuit




## TYPICAL PERFORMANCE CHARACTERISTICS


(1) Forward Voltage vs. Forward Current




(2) Reverse Voltage vs. Reverse Current




(3) Ambient Temperature vs. Forward Voltage




(4) Ambient Temperature vs. Reverse Current




(5) Reverse Voltage vs. Inter-Terminal Capacity



(6) Ambient Temperature vs. Average Forward Current




## ■ PACKAGING INFORMATION



SOD-123

## ■ MARKING RULE

### ● SOD-123



- ① 1 (Product Number)
- ② Assembly Lot Number

1. The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this catalog is up to date.
2. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this catalog.
3. Please ensure suitable shipping controls (including fail-safe designs and aging protection) are in force for equipment employing products listed in this catalog.
4. The products in this catalog are not developed, designed, or approved for use with such equipment whose failure of malfunction can be reasonably expected to directly endanger the life of, or cause significant injury to, the user.  
(e.g. Atomic energy; aerospace; transport; combustion and associated safety equipment thereof.)
5. Please use the products listed in this catalog within the specified ranges.  
Should you wish to use the products under conditions exceeding the specifications, please consult us or our representatives.
6. We assume no responsibility for damage or loss due to abnormal use.
7. All rights reserved. No part of this catalog may be copied or reproduced without the prior permission of Torex Semiconductor Ltd.

**TOREX SEMICONDUCTOR LTD.**